

5294/USSN 09/601,842
Group Art Unit 1733

AMENDMENTS TO THE CLAIMS

ABC
Claims 1-49 (~~Previously~~ Canceled).

50. (Canceled).

51. (Canceled).

ABC
52. (~~Previously~~ Canceled).

ABC
53. (~~Previously~~ Canceled).

54. (Canceled).

55. (Currently Amended) A method for producing an embossed sheet material including at least two layers of web material joined together, comprising steps of:

- embossing a first layer of web material, previously provided with a background pattern made up of a first set of protuberances, so as to generate on the first layer a second set of protuberances, which are partially superimposed on the first set of protuberances making up the background pattern, and defining an ornamental motif made up of a pattern of major dimensions and minor density with respect to the background pattern,

- embossing a second layer of web material for generating thereon a third set of protuberances having the same density as the protuberances of said second set,

- coupling by means of adhesive to said first layer of web material at least said second layer of web material,

5294/USSN 09/601,842
Group Art Unit 1733

- wherein the adhesive is applied to a top surface of at least some protuberances of said third set of protuberances, the sheet material being substantially free of adhesive in correspondence with protuberances of said first set of protuberances forming said background pattern,

- wherein protuberances of said second set and said third set are inserted inside one another,

- wherein said first set of protuberances and said second set of protuberances are generated on the first layer by running said first layer around a first pressure roller interacting with a first embossing cylinder and a second embossing cylinder that have respectively a first set of points and a second set of points, the second set of points being of larger dimension and lower density than the first set of points, and

- wherein ~~The method according to claim 54~~ further comprising joining together said first layer and said second layer are joined together between the first pressure roller and the second embossing cylinder that interacts with the first pressure roller.

56. (Currently Amended) The method according to claim ~~54~~ or 55 wherein said second embossing cylinder interacts with a second pressure roller to generate a third set of protuberances on said second layer.

57. (~~Previously Canceled~~).

5294/USSN 09/601,842
Group Art Unit 1733

58. (Currently Amended) The method according to claim ~~54~~ or 55 further comprising embossing said second layer with a greater embossed depth than an embossed depth of the second set of protuberances on the first layer.

59. (Currently Amended) A method for producing an embossed sheet material including at least two layers of web material joined together, comprising steps of:

- embossing a first layer of web material,
previously provided with a background pattern made up of a
first set of protuberances, so as to generate on the first
layer a second set of protuberances, which are partially
superimposed on the first set of protuberances making up the
background pattern, and defining an ornamental motif made up
of a pattern of major dimensions and minor density with
respect to the background pattern,

- embossing a second layer of web material for
generating thereon a third set of protuberances having the
same density as the protuberances of said second set,

- coupling by means of adhesive to said first
layer of web material at least said second layer of web
material,

- wherein the adhesive is applied to a top surface
of at least some protuberances of said third set of
protuberances, the sheet material being substantially free

5294/USSN 09/601,842
Group Art Unit 1733

of adhesive in correspondence with protuberances of said first set of protuberances forming said background pattern,

- wherein protuberances of said second set and said third set are inserted inside one another,

- wherein said first set of protuberances and said second set of protuberances are generated on the first layer by running said first layer around a first pressure roller interacting with a first embossing cylinder and a second embossing cylinder that have respectively a first set of points and a second set of points, the second set of points being of larger dimension and lower density than the first set of points, and ~~The method according to claim 54 further comprising running~~

- wherein said second layer is run around said first pressure roller, downstream of an area in which the first layer is embossed between said first embossing cylinder and said first pressure roller, and embossing said second layer on said first layer between the first pressure roller and the second embossing cylinder.

60. ^{Presented} ~~(Previously Added)~~ The method according to claim 59 further comprising arranging a second pressure roller around the second embossing cylinder and feeding a third layer of web material around said second pressure roller, between the second pressure roller and the second embossing cylinder, so as to generate a fourth set of protuberances on

5294/USSN 09/601,842
Group Art Unit 1733

the third layer, and the first layer, the second layer and the third layer being laminated together between the second embossing cylinder and the second pressure roller.

61. ^{presented} (Previously ~~Added~~) The method according to claim 60 further comprising applying an adhesive to at least some protuberances of said second set of protuberances and adhering together the first layer, the second layer and the third layer by causing the adhesive to migrate through the first layer toward the second layer.

62. (Canceled).

63. (Canceled).

64. (Canceled).

65. (~~Previously Canceled~~).

66. (~~Previously Canceled~~).

67. (Canceled).

68. (Currently Amended) A method for producing an embossed sheet material including at least two layers of web material joined together, comprising steps of:

- embossing a first layer of web material,
previously provided with a background pattern made up of a first set of protuberances, so as to generate on the first layer a second set of protuberances, which are higher than and partially superimposed on the first set of protuberances making up the background pattern, and defining an ornamental motif made up of a pattern of major dimensions and minor

5294/USSN 09/601,842
Group Art Unit 1733

density with respect to the background pattern, said first set of protuberances and said second set of protuberances protruding from a common face of said first layer; and

- coupling by means of adhesive to said first layer of web material at least a second layer of web material,

- wherein the adhesive is applied in areas corresponding to at least some protuberances of said second set of protuberances, the sheet material being substantially free of adhesive in correspondence with protuberances of said first set of protuberances forming said background pattern,

- wherein said second layer of web material is provided with a background pattern made up of a set of protuberances,

- wherein said first layer and said second layer are separately embossed by corresponding first and second embossing units, which generate protuberances forming the background pattern on the first layer and the second layer, and are then run around a first embossing cylinder provided with points for generating said ornamental motif on the first layer and for joining the first layer and the second layer, The method according to claim 67

- wherein said first layer is embossed according to said background pattern between a pair of rollers of a first embossing unit and is subsequently embossed on a said first

5294/USSN 09/601,842
Group Art Unit 1733

embossing cylinder provided with points for generating said ornamental motif, and

- wherein the second layer is embossed between a second embossing cylinder and a pressure roller of said second embossing unit, said second embossing cylinder being provided with points for generating said background pattern on the second layer and wherein the first layer and the second layer are joined between said first embossing cylinder and said second embossing cylinder.

69. (Canceled).

70. (Canceled).

71. (Canceled).

HC 72. (Previously ^{presented} ~~Added~~) The method according to claim 56 further comprising applying an adhesive to at least some protuberances of said third set on said second layer, and joining said first layer and said second layer by adhering said first layer and said second layer together, with protuberances of said third set in correspondence with protuberances of said second set.

73. (Canceled).

HC 74. (~~Previously~~ Canceled).

75. (Canceled).

HC 76. (~~Previously~~ Canceled).

77. (Canceled).

78. (Canceled).

5294/USSN 09/601,842
Group Art Unit 1733

79. (Canceled).

80. (Canceled).

81. (Canceled).

82C 82. (Previously ^{Presented} ~~Added~~) The method according to claim 68 wherein said first layer and said second layer are joined together by a colored adhesive.

83C 83. (~~Previously~~ Canceled).

84. (Canceled).

85C 85. (~~Previously~~ Canceled).

86. (Canceled).

86C 87. (~~Previously~~ Canceled).

88. (Canceled).

89. (Canceled).

90. (Canceled).

91. (Canceled).

92C 92. (Previously ^{Presented} ~~Added~~) A method for producing an embossed sheet material including at least two layers of web material joined together, comprising steps of:

- embossing a first layer of web material, previously provided with a background pattern made up of a first set of protuberances, so as to generate on the first layer a second set of protuberances, which are partially superimposed on the first set of protuberances making up the background pattern, and defining an ornamental motif made up of a pattern of major dimensions and minor density with

5294/USSN 09/601,842
Group Art Unit 1733

respect to the background pattern, wherein the background pattern on the first layer of web material is provided by embossing in-line and before the embossing of the first layer for generating said ornamental motif,

- coupling by means of adhesive to said first layer of web material at least a second layer of web material, wherein the adhesive is applied in areas corresponding to at least some protuberances of said second set of protuberances, the sheet material being substantially free of adhesive in correspondence with protuberances of said first set of protuberances forming said background pattern,

- generating said first set of protuberances and said second set of protuberances on the first layer by running said first layer around a first pressure roller interacting with a first embossing cylinder and a second embossing cylinder that have respectively a first set of points and a second set of points, the second set of points being of larger dimension and lower density than the first set of points, and

- joining together said first layer and said second layer between the first pressure roller and the second embossing cylinder that interacts with the first pressure roller.

5294/USSN 09/601,842
Group Art Unit 1733

SPC
93. (Previously ~~Added~~ ^{Presented}) The method according to claim 92 wherein said second embossing cylinder interacts with a second pressure roller to generate a third set of protuberances on said second layer.

94. (Canceled).

SPC
95. (Previously ~~Added~~ ^{Presented}) A method for producing an embossed sheet material including at least two layers of web material joined together, comprising steps of:

- embossing a first layer of web material, previously provided with a background pattern made up of a first set of protuberances, so as to generate on the first layer a second set of protuberances, which are partially superimposed on the first set of protuberances making up the background pattern, and defining an ornamental motif made up of a pattern of major dimensions and minor density with respect to the background pattern, wherein the background pattern on the first layer of web material is provided by embossing in-line and before the embossing of the first layer for generating said ornamental motif,

- coupling by means of adhesive to said first layer of web material at least a second layer of web material, wherein the adhesive is applied in areas corresponding to at least some protuberances of said second set of protuberances, the sheet material being substantially free of adhesive in correspondence with protuberances of

5294/USSN 09/601,842
Group Art Unit 1733

said first set of protuberances forming said background pattern,

- generating said first set of protuberances and said second set of protuberances on the first layer by running said first layer around a first pressure roller interacting with a first embossing cylinder and a second embossing cylinder that have respectively a first set of points and a second set of points, the second set of points being of larger dimension and lower density than the first set of points, and

- running said second layer around said first pressure roller, downstream of an area in which the first layer is embossed between said first embossing cylinder and said first pressure roller, and embossing said second layer on said first layer between the first pressure roller and the second embossing cylinder.

96. ^{Reserved} (Previously ~~Added~~) The method according to claim 95 further comprising arranging a second pressure roller around the second embossing cylinder and feeding a third layer of web material around said second pressure roller, between the second pressure roller and the second embossing cylinder, so as to generate a fourth set of protuberances on the third layer, and the first layer, the second layer and the third layer being laminated together between the second embossing cylinder and the second pressure roller.

5294/USSN 09/601,842
Group Art Unit 1733

97C 97. (Previously ^{Revised} ~~Added~~) The method according to claim 96 further comprising applying an adhesive to at least some protuberances of said second set of protuberances and adhering together the first layer, the second layer and the third layer by causing the adhesive to migrate through the first layer toward the second layer.

98C 98. (Previously ^{Revised} ~~Added~~) The method according to claim 93 further comprising applying an adhesive to at least some protuberances of said third set on said second layer, and joining said first layer and said second layer by adhering said first layer and said second layer together, with protuberances of said third set in correspondence with protuberances of said second set.

99. (Currently Amended) A method for producing an embossed sheet material including at least two layers of web material joined together, comprising steps of:

- embossing a first layer of web material, previously provided with a background pattern made up of a first set of protuberances, so as to generate on the first layer a second set of protuberances, which are partially superimposed on the first set of protuberances making up the background pattern, and defining an ornamental motif made up of a pattern of major dimensions and minor density with respect to the background pattern,

5294/USSN 09/601,842
Group Art Unit 1733

- coupling by means of adhesive to said first layer of web material at least a second layer of web material,

- wherein the adhesive is applied in areas corresponding to at least some protuberances of said second set of protuberances, the sheet material being substantially free of adhesive in correspondence with protuberances of said first set of protuberances forming said background pattern,

- wherein said second layer of web material is provided with a background pattern made up of a set of protuberances,

- wherein said first layer and said second layer are separately embossed by corresponding first and second embossing units, which generate protuberances forming the background pattern on the first layer and the second layer, and are then run around ~~an~~ a first embossing cylinder provided with points for generating said ornamental motif on the first layer and for joining the first layer and the second layer, and

- wherein ~~one of~~ said first layer ~~or said second layer~~ is embossed according to said background pattern between a pair of rollers of a first embossing unit and is subsequently embossed on ~~an~~ said first embossing cylinder provided with points for generating said ornamental motif, and wherein the second layer is embossed between a further

5294/USSN 09/601,842
Group Art Unit 1733

second embossing cylinder and a pressure roller of said
second embossing unit, said further second embossing
cylinder being provided with points for generating said
background pattern on the second layer and wherein the first
layer and the second layer are joined between said first
embossing cylinder and said second embossing cylinder.

100. (Previously ^{Presented} ~~Added~~) The method according to claim
99 wherein said first layer and said second layer are joined
together by a colored adhesive.

101. (Canceled).

102. (Canceled).

103. (Canceled).